$\bigcirc \bigcirc \bigcirc$

Voltage Detector

Protect yourself and other technicians by using this simple device to test conductive objects and within minutes, you can avoid exposure to high voltage electrical shock. Compact, lightweight and easy to use, the Voltage Detector is recommended for use in the field when working near potentially dangerous objects including:

• Transformer cases

FLUKE

networks

- Circuit breaker housing
- Power ground wires
- Street light fixtures
- Mobile homes
- Metal frameworks
- Metal conduit
- Pedestals
- Newly-driven ground rods
- Metallic siding homes
- Electrical machinery



Specifications

Size	12" L x 1.5" D (30.48 cm x 3.81 cm)
Weight	1 lb (454 g)
Low voltage	A red LED will flash for 50 VAC RMS
threshold	and higher or for 6 VDC and higher
High voltage	Protects users up to 20,000 VAC
threshold	RMS or 2,000 VDC

Ordering Information

C9970	Voltage Detector and probe cap
C9973	Voltage Detector Kit (includes Voltage Detector, probe cap, storage bag, tem porary bond, ground cord, and handbook)
C9974	Voltage Detector Kit with Test Probe

Accessories and options

C9964	Handbook
C9965	Probe Cap
C9966	Test Plug
C9967	Ground Cord
C9970H	Holster
C9971	Storage Bag
C9972	Temporary Bond

Simple design for ease-of-use

The Voltage Detector detects ac and dc voltages through a long-life carbide tip, which is protected by a plastic cap when not in use. To use the Voltage Detector, you simply place the carbide tip on the object in question, press the magnetic trigger, and observe the LEDs. If the green LED illuminates, the surface being touched is free from electrical hazards. If the red LED flashes, dangerous voltage is present.

N E T W O R K S U P E R V I S I O N

Fluke Networks, Inc. P.O. Box 777, Everett, WA USA 98206-0777

Fluke Europe B.V. P.O. Box 1186, 5602 BD Eindhoven, The Netherlands

For more information call:

U.S.A. (800) 283-5853 or Fax (425) 446-5043 Europe/M-East/Africa (31 40) 2 675 200 or Fax (31 40) 2 675 222 Canada (800) 363-5853 or Fax (905) 890-6866 Other countries (425) 446-4519 or Fax (425) 446-5043 E-mail: fluke-assist@flukenetworks.com Web access: http://www.flukenetworks.com

©2001 Fluke Networks, Inc. All rights reserved. Printed in U.S.A. 8/2001 1278867 A-ENG-N Rev C