

BTU1500



Built with Quality in Mind

The Latest in Combustion Analysis Technology

Residential & Commercial COMBUSTION ANALYZER

Accurate

Reliable

Robust

Fast

CO₂

CO

O₂



- 6 Tools-In-One
- Draft & Differential Pressure
- Flue & Ambient Temp
- Ambient CO Monitor
- Built-In Manometer
- Combustion Efficiency
- PC Software w/ Auto Saving
- Unbreakable Metal Connections



NEW!



NEW!

Automatic, TRUE High-Efficiency Calculations for ALL Condensing Systems



BUILT-IN Printer

Full COLOR Graphic Display

Field Replaceable Sensors

E Instruments International

www.E-Inst.com

P: 215-750-1212 F: 215-750-1399 A: 402 Middletown Blvd, Ste 216 Langhorne, PA 19047

BTU1500 Features



Built with Quality in Mind

**BUILT-IN PRINTER
(NON-Fading Paper)**

**Full COLOR
Graphic Display**

**Simple Menu
Interface**



**Magnetic
Rubber Holster**

**Pre-Calibrated
Field Replaceable
Sensors**

**Unbreakable Metal
Connections**

NEW!

**Automatic Outdoor
Air Temp. & High-
Efficiency Calculations
(Condensing Systems)**



Bluetooth

Download on the
App Store

ANDROID APP ON
Google play

**PC Software, Bluetooth,
& App Included**



**Large Color
Graphic Display**

**All BTU1500 Kits
Include:**

- New iOS & Android App
- New Auto Outdoor Air Temp.
- Built-In Printer
- Large Color Display
- O₂, CO, CO₂
- Combustion Efficiency, Losses, Excess Air
- CO Air Free
- Draft & Differential Pressure
- Temperature Measurements
- 2000 Test Internal Memory
- Bluetooth Connectivity
- Long Lasting Rechargeable Battery & AC Charger
- Gas Sampling Probe & Hose
- Water Trap with Filter Cartridge
- Magnetic Rubber Holster
- PC Software & USB Cable
- Operating Manual
- Calibration Certificate
- Carrying Case

Parameter	Sensor	Range	Resolution	Accuracy
O ₂	Electrochemical	0 - 25 %	0.1 %	±0.2 % vol
CO H ₂ Compensated w/ Built-In NO _x Filter	Electrochemical	0 - 8000 ppm	1 ppm	±8 ppm <400 ppm ±5 % rdg up to 2000 ppm ±10 % rdg for >2000 ppm
CO ₂	Calculated	0 - 99.9%	0.1 %	
Tair	Pt100	-10 to 212 °F	0.1 °F	±1 °F
Tgas	Tc K	-10 to 1830 °F	0.1 °F	±2 °F
Differential Temp.	Calculated	-10 to 1830 °F	0.1 °F	
Pressure/Draft	Semiconductor	±0 - 80 inH ₂ O	0.001 inH ₂ O	±1 % rdg.
Excess Air	Calculated	0 - 850%	1 %	
Efficiency	Calculated	0 - 100%	0.1 %	
Warranty	2 years: Analyzer + Sensors			

Ordering Information

Model No.	Description
1500-1	BTU1500 Base Kit = Analyzer w/ O ₂ , CO, CO ₂ , Efficiency, Excess Air, Draft, Pressure, Temp, Rechargeable Battery & AC Plug, 10' Dual Hose, 12" Probe, Vinyl Case, Calibration Certificate, Operating Manual, Cheat Sheet, Water Trap, Paper Roll, 2000 Internal Data Storage, PC Software, Bluetooth™ Connectivity, Automatic Outdoor Air Temperature Saving for ALL 90%+ Systems & Condensing Systems for TRUE Efficiency Calculations + Built-In Printer + New iOS and Android App Included
1500-Oil	Standard 1500-1 Kit PLUS: Oil Smoke Pump , Smoke Filter Papers, and Comparison Chart
1500-DP	Standard 1500-1 Kit PLUS: Differential Pressure Manometer Kit (2 Hoses)

E Instruments International

www.E-Inst.com

P: 215-750-1212 F: 215-750-1399 A: 402 Middletown Blvd, Ste 216 Langhorne, PA 19047

